


Integrated measuring systems
for the whole water cycle



Transit Time Flowmeter

ChronoFLO POCKET



Compact and portable
flow meter

8 hours of continuous
operation

Quick and easy
installation

Diameter range: 15
mm up to 6000 mm

Non invasive flow
measurement

For more information call +852 3746 9033
or visit www.alliedpower.com.hk

Allied Power
We Empower Your Business

HYDREKA
www.hydreka.fr

Application

The ChronoFLO POCKET is the latest version of our well-known ChronoFLO line of products. Available as a dedicated or a portable version, the ChronoFLO POCKET is an ideal permanent or temporary equipment to monitor flow and volume (metering at different locations on drinking water systems, meter testing...).

Key Benefits :

- A wide diameter range from 15 mm up to 6000 mm
- Rapid installation
- Compact and ultra light product
- Display unit: flow, total flow (both directions), velocity and signal quality
- Built in data logger



Technical Specifications	Description
<i>Accuracy</i>	Linearity : < 0.5%, Repeatability: < 0.2%, accuracy : +/- 1%
<i>Outside Diameter range</i>	15 mm up to 6000 mm. Three set of sensors.
<i>Languages</i>	Selectable: English or Italian
<i>Ingress Protection</i>	central unit: IP20 ; Sensors with BNC connectors: IP 20
<i>Power Supply</i>	3 AAA Built-in rechargeable NI-MH batteries, provide over 12 hours of continuous operation. Charger 100-240 VAC + adapter.
<i>Dimensions and Weight</i>	210 x 90 x 30 mm; Weight: 0.5 Kg
<i>Large LCD Display</i>	4x16 characters for real time flow, Total Flow (Positive, Negative and Net), Velocity, Status etc...
<i>Communications</i>	RS232
<i>Data logger</i>	Built-In 24 K Data Logger. Can store over 2000 lines of data
<i>Standard Configuration</i>	1 Hand-held Unit ; 2 sets of clamp-on sensors ; Transducer Cables ; 2 Stretcher (3 meters) ; 1 Data Line ; 1 Power Cord ; 1 Carrying Case
<i>Ultrasonic Thickness Gauge</i>	Accuracy: +/- 0.5% Resolution: 0.1 mm Thickness range: 1.2 mm to 225 mm Dimensions: 120x62x30 mm Weight : 164 g without battery Communication: RS232 Interface Power supply : 4x1.5V AAA

Products available to rent or buy. Please contact us for more information.

Allied Power

We Empower Your Business

HYDREKA
www.hydreka.fr

Tel: +852 3746 9033
Fax: +852 852 2120 8765
Email: contact@alliedpower.com.hk

Unit B, 11/F Long To Building,
654-656 Castle Peak Road,
Lai Chi Kok, Kowloon, Hong Kong

A HALMA COMPANY

www.alliedpower.com.hk